

Technical Specifications		General Information
		<b>Pile reversal:</b> All cut pile carpets can suffer from
Construction	Woven Axminster	pile reversal and in certain instances this may
Pitch	7 per inch/27.6 per dcm	become permanently bent or distorted for no specific
Rows	8 per inch/31.4 per dcm	reason that research has yet identified, giving areas
Finished pile height (+/- 1mm)	7.5mm	of light and shade. This ia also known as "shading"
Gross total pile weight (+/- 10%)	1225g/m2	or "watermarking". It is not a defect in manufacture
Finished total carpet weight (+/- 15%)	2070 g/m2	it only occurs in a small percentage of all carpets
Tuft density per m2 (+ 10%, -7.50%)	86,940	and no liability whatsoever can be accepted by the
Yarn type (+/- 3%)	80% Wool, 20% Nylon	manufacturer in respect of it.
Yarn count & tex	2 ply/47's, R660 tex	
Backing	Woven Polyester/polypropylene	<b>Pile pressure:</b> All cut pile carpets are liable to show
Width (+/- 1.25%)	4.00m	light and dark patches resulting from disturbance
		of the pile created by foot traffic or brushing. This is
		a normal feature and is not a defect in manufacture
<b>Tested for</b>		and no liability whatsoever can be accepted by the
<b>Suitability</b>		manufacturer in respect of it.
Extra heavy domestic / heavy contracty		
		<b>Pale shades:</b> We include within our collection a
Flammability	(in accordance with clause 11	number of pale shades. Primarily these are used as
Fire behaviour	of EN13501-1:2002)	top or highlight colours. These more delicate shades
Smoke production	(BS4790 BS5287)	will invariably tend to soil more quickly and give a
		lower of light fastness than the norm, and may show
<b>Castor chair</b>		natural blemishes within the fibre that tend to be

Not recommended unless protecting mat is present			masked in deeper shades containing a greater quantity of dyestuff.
<b>Suitability for stairs</b>	(in accordance with BS EN1307)		<b>Maintenance</b>
Yes (For maximum performance we recommend the use of an approved stair nosing and the movement of carpet every 6 months from tread to rise)			We recommend that this carpet is maintained in accordance with an agreed maintenance schedule which should include the following:
			i). Vacuum regularly
			ii). Remove spills immediately
			iii). Professionally clean as required
<b>Installation</b>			
To be installed in accordance with BS5323 "Code of Practice for the installation of Floor Coverings" and NICF manual.			
For quantity orders requiring colour matching, please state at the time of ordering			
All samples may not be from the same production batch as current stock and therefore should be used as a guide and not as an exact match.			